WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

G06K 19/067, G07F 7/10

10

A1

(11) International Publication Number:

WO 91/10971

(43) International Publication Date:

25 July 1991 (25.07.91)

(21) International Application Number:

PCT/SE90/00032

(22) International Filing Date:

15 January 1990 (15.01.90)

(71) Applicant (for all designated States except US): UTVECK-LINGS AB JONIC [SE/SE]; Karl Jonasson, Helsingegatan 14-16 D, S-113 23 Stockholm (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SJÖBLOM, Hans, Olof [SE/SE]; Lojovägen 9, S-181 47 Lidingö (SE).

(74) Agents: GRAHN, Thomas et al.; Oscar Grahn Patentbyrå AB, P.O. Box 19540, S-104 32 Stockholm (SE).

(81) Designated States: AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH (European patent), CM (OAPI patent), DE (European patent)*, DK (European patent), ES (European patent), FI, FR (European patent), GA (OAPI patent), GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL (European patent), NO, RO, SD, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US.


Published

With international search report.
In English translation (filed in Swedish).

(54) Title: HANDLING SYSTEM FOR INFORMATION CARRIERS

(57) Abstract

The present invention relates to a handling system for information carriers such as credit cards (1) and the like, including information storing means such as chip circuits (4) and the like. The essence of the invention resides in the feature that a credit card, when not used, is to be unserviceable. To activate a credit card to serviceable condition there is introduced into the chip circuit, by a code transmitter (Fig. 3), one or more states of authority, which are adapted to be read by a transceiver device (28) included in a press copying machine for credit cards (18, Fig. 4). The authority information received is arranged to be indicated (35) at the press copying machine. The press copying operation is also arranged to control the transceiver device (28) such that a signal is transferred to the chip circuit (4-6) to extinguish the state therein, that is, to deactivate the credit card after authority indication.



* See back of page

DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria		*		
AU		ES	Spain	MG	Madagascar
	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia .
BE	Belgium	GA	Gabon ·	MR	Mauritania
BF	Burkina Faso .	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL.	
BJ	Benin	GR			Netherlands
BR ·	Brazil		Greece	NO	Norway
CA		HU	Hungary	PL	Poland
	Canada	!T	lialy .	RO	Romania
CF	Central African Republic	JP	Japan '	SD	Sudan
cc	Congo	· KP	Democratic People's Republic	SE	Sweden
CH	Switzerland		of Korea	SN	Senegal .
CI	Côte d'Ivoire	KR.	Republic of Korea		
CM.	Cameroon	LI	11	ะรบ	Soviet Union
.cz	Czechoslovakia			TD	Chad
. DE		LK .	Sri Lanka .	TC	Togo
	Germany	LU	Luxembourg .	US	United States of America
DK	Denmark	MC	Monaco		

WO 91/10971

Handling System for Information Carriers

Technical field

The present invention relates to apparatus and systems for cooperation with credit cards and the like. In the present context the term credit card is intended to cover all forms of information carriers which are portable and which can receive and give off information.

Prior art

Nowadays various forms of identity and credit cards are generally used, most of them including, besides visually readable information such as the card owner's name etc., some form of information carrier, readable by electronic means. Said type of information carrier usually comprise a tape of magnetic material into which a signal code is introduced, said code being readable for identification purposes by electromagnetic means and electronic apparatus connected thereto. An example hereof is so called "Bankomat" (an automatic cash dispenser) cards and card reading machines associated therewith.

There are also credit cards and identification documents today which include electronic circuits, so called chips, which in turn include memory and signal processing circuits. These chips are provided with means for receiving and emitting signals from and to outside transmission means. Consequently, by means of this technique information can be stored in the memory of the chip circuits, to be utilized in various ways. Among the public such credit cards are now called "smart cards". The advantage of e.g. credit cards provided with such chips is the feature that when using the card, for instance, as a "Bankomat" card or an account card in department stores, direct information of the owner's credit worthiness can be obtained, provided that the point of sale concerned is connected to a banking centre, e.g. via modems and telecommunication networks. For example, between said chips and the banking centre such communication can be established that the purchase sum at any time of buying is automatically deducted from the credit amount available, and is restored in the memory of the chip circuit to be used again at the next point of purchase.

15

10

20

25

30

15

20

25

30

35

A credit card operating and used in this way will of course mean excellent security to shopkeepers as well as the bank, in—asmuch as control functions can be established in a very reliable way. The level of security in the present connection is thus very high. However, a considerable disadvantage of a system as disclosed above is the fact that each point of sale has to be equipped with a terminal connected by modems to a banking centre, e.g. by way of telecommunication circuits or leased circuits. As a matter of course it will be very costly for a department store to install a terminal at every cash desk. Also, the loading of the telecommunication network will also be considerable. However, such systems have been tested in practice and found to be secure but they are, as stated, expensive to install as well as to run. The credit cards proper, however, are comparatively cheap to produce, even if they are provided with a chip.

In to-day's situation a credit card can be used many times over if an unauthorized person gets hold of it. The time before one manages to freeze a card can vary from a few hours to a week, which of course is very unfavourable to the card owner. The economical loads on card owners as well as on account card enterprises are considerable. Much would be gained if a level of security could be attained in everyday handling which approaches that exhibited by credit cards with chips according to the above. Essential is to prevent unauthorized persons from using another person's credit card.

Summary of the invention

The present invention is based upon a novel idea, namely, to render a credit card or similar information carrier unvalid for payment as long as the owner does not take special measures to bring the card into a state of validity. According to the invention the owner has at his disposal a code transmission apparatus which can be communicated with a memory circuit included in the credit card or the like for transferring a specific validity code to render the card serviceable. A credit card brought into this state is intended to be put in cooperation with a further transmission apparatus, e.g. mounted in a so called imprinter at a point of sale, for reading the memory contents of the chip circuit. The transmission circuit is adapted to extinguish, after

.15

20

25

30

35

having received the validity code, the memory contents of the chip circuit. The procedure thus described is arranged to trigger indicating means so that the point of sale or the like concerned will obtain an indication that the card is valid as a means of payment. When the card is given back to the owner there are thus no validity markings, which means that if some unauthorized person should get hold of the card this cannot be used. Any corresponding apparatus at any point of sale would give rise to an indication of unvalidity. As can be seen, the credit card in question will be completely unfit for use as long as the owner does not activate the card.

The characterizing features of the present invention will appear from the patent claims that follow.

The invention will be described in greater detail with reference to the accompanying drawings which show and exemplify an embodiment of the invention.

List of figures

Fig. 1 shows a credit card having an internal chip circuit. Fig. 2 shows diagrammatically the chip circuit according to Fig. 1 in communicative cooperation with a transmission device for signal transfer.

Fig. 3 shows the credit card according to Fig. 1 with its chip circuit in cooperation with an activating device.

Fig. 4 shows diagrammatically and in perspective a press copying machine for credit cards equipped in accordance with the present invention and including signal transmission devices for communication with the chip circuit.

Description of embodiments

The credit card 1 shown in Fig. 1 is provided in the usual way with markings for identification, generally impressed and stating the owner's name and identification number. The reverse side of the credit card 1 contains a magnetic strip 3 intended to cooperate with reading means, for example, occurring in connection with "Bankomat" terminals. The credit card also includes a chip circuit 4 with a signal transferring means 5 and a memory circuit 6. The chip circuit also contains signal processing units, but for the sake of clarity such circuit members have been omitted. Consequently the chip circuit is illustrated completely

diagrammatically.

As pointed out in the introduction a chip circuit can be supplied with a state of signal which can be stored in its memory. Fig. 2 shows a transmission device for the inductive transfer of states of signal to the chip circuit proper. In order that states of signal be possible to transfer a coil 7 is used for inductive cooperation with the signal transferring means 5. Said coil 7 is in communication, by cables 8, with a transceiver arrangement 9 including signal processing circuits. The arrangement 9 communicates with an indicator means 10 including a display screen 11. By activating the transceiver arrangement 9 activating signals can be transferred inductively by way of coil 7 to the receiving means 5 in order to make it possible that the chip circuit in turn be activated and states of signal possibly be stored in the memory circuit 6. The communication can be bidirected, that is, upon certain commands the chip circuit can respond and submit to the transceiver arrangement 9 states of signal which can be visualized on the display 11. Consequently, information can be stored in the memory curcuit 6 which is significant to the use of the credit card in connection with e.g. a terminal.

As stated above the essence of the invention resides in the feature that a credit card or some other information carrier in its normal condition is to be inactive or exhibit some state of information indicating that the card concerned is unserviceable. This means that the card has to be activated, that is, be brought into such a state that it can be used as means of payment. To this end the card is presented to an activating device. Such an activating device is illustrated in Fig. 3 and designated 12. The activating device includes four operating keys 13, 14, 15, 16 each connected to a signal processing and transmitting circuit 17 included in the activating device. Although not shown in detail the circuit 17 includes similar devices as those shown in Fig. 2, that is 7, 8 and 9, for cooperation with the receiving means 5 in the chip circuit 4. Fig. 3 illustrates how the credit card is brought together with the activating device so that a state of signal can be transferred from the activating circuit to the memory 6 of the chip circuit 4. Introducing a code signal

30

10

15·

20

25

sequence forming a state of activation in the memory 6 could suitably be triggered by a specific sequential depressing of the operating keys 13-16. For example, to the card owner and user an operating sequence could be such that first the operating key 15 is depressed. Then 13, followed by 14 and 16. After such an operation a state of signal has thus been transferred to the memory circuit 6, and the card is now to be considered serviceable. The user can thus remove the card from the activating device 12 and leave the card to a point of sale as a means of payment.

In fig. 4 there is diagrammatically shown a press copying machine, i.e. a device for transferring by pressure embossed information from a credit card to a bundle of debiting and checking blanks for the customer to confirm and attest. The press copying machine 18 shown in the figure has the form of a box having an upper frame 19 defining a lowered surface 20 with a recess for receiving the credit card 1 concerned. On the edges 19 of the frame a press copying mechanism 21 is arranged slidable and displaceable along the box in the directions of arrows 22 and 23. The press copying mechanism 21 includes in the usual manner a pressure roll 24 and an operating handle 25 at the top. By dot-dashed lines there is indicating said bundle of checking and debiting blanks 26 to be inserted in the direction of arrow 27 on top of the credit card and onto the lowered surface 20. In operating the mechanism 21, i.e. displacing it in the direction of arrow 22, the pressure roll 24 will press the blanks against the credit card and perform imprinting.

However, in accordance with the present invention the machine 18 illustrated is provided in its box-shaped part with a transceiver device 28 and associated transmission details 29. The apparatus now described is located such that communication can be established between the chip circuit 4 and the transceiver device 28. A change-over switch 30 is connected to the transceiver device 28 by a cable 29, the switch having an operating rod 31 carrying an operating button 32 projecting somewhat above the surface of the frame 19. The device 28 communicates by a cable 33 with an indicating device 34 with an indicating display screen 35.

30

25

10

15

It is assumed, as described in connection with Fig. 3, that the activated credit card is inserted into the press copying machine 18 shown in Fig. 4 on the spot marked for the purpose, after which the bundle of debiting blanks 26 is inserted and the pressure mechanism 21 set in motion in the direction of arrow 22 by the handle 25 being operated. According as the mechanism slides along the two sides of the frame 19 the pressure roll 24 will press the bundle 26 against the credit card and impression occurs as usual. When the pressure mechanism 21 has arrived to the operating button 32 this will be actuated by a force causing the switch 30 to be reversed, which has the effect that the transceiver device 28 is started and emits an inquiry signal sequence which is transferred to the chip circuit 4 in the manner previously disclosed. Hereby the chip circuit arrives into operating position and opens the memory circuit towards the transceiver device 28. The state previously applied to the memory of the chip circuit is now communicated to the device 28 which will read said state. If the state exhibits a predetermined value, a signal is transmitted to the indicating unit 34. Then the display 35 is being lit and an indication shows, for example, by the letters "Valid", that the credit card in question is serviceable. When the pressure device 21 has been pushed all the way to the opposite end of the machine 18 the operating push button 32 is again released and the transceiver circuit 28 returns to a resting position. In order to make it possible to remove the bundle 26 the pressure mechanism 21 has to be returned to the starting position shown in Fig. 4. In doing so the pressure mechanism 21 will again actuate the operating button 32 with the result that the transceiver 28 is switched to transmitting position. A code signal is then emitted and transmitted to the chip circuit 4, said code signal causing the state earlier applied to the memory 6 to be extinguished. Hence, when the credit card is given back to the customer it is unfit for use but, still, it has served its purpose by having given the point of sale a go-ahead signal to the effect that it has been possible to use the card at the moment of sale. The credit card can now be kept by the owner without being under any particular supervision, as the card, should it be used

30

25

10

15

20

15.

20

25

30

35

improperly at any point of sale, would be unable to create any go-ahead signal on the indicating display 35.

As shown, a credit card, otherwise a booty attracting thieves, can be made worthless in very simple way, as the user normally maintains the credit card inactive, that is, unserviceable. A press copying machine equipped in a manner shown in Fig. 4 represents a modest investment indeed in comparison with the installation of a bank associated terminal with modems and the like at every point of sale. As pointed out earlier security will of course not be quite the same as when terminals are used, still, misuse of the credit card by unauthorized persons can be largely prevented.

In order to further raise the safety level such solutions can of course be conceived where the credit card magnet strip 3 mentioned earlier is read by means, not shown in detail, when the pressure mechanism 21 is displaced. Then the code information obtained by reading the contents of the magnet strip 3 together with code contents of the memory 6 of the chip circuit 4 can form parameters for a comparison of information, which in turn can result in triggering the indicating device 34 so that the display 35 will indicate a serviceable credit card. In such a connection the security level will of course be raised considerably.

Within the scope of the invention the security level can be raised further by the following measures relating to the press copying machine proper. As mentioned before the contents of the memory of the chip circuit 4 is read in connection with the credit card being press copied. Besides the fact that a state is imparted to the memory indicating that the card is serviceable it is conceivable that information has been introduced into the memory about the recording of the credit card with the credit card company concerned. Such information can be readily stored in a memory in the means 28. As mentioned before, returning the press copying mechanism 21 is intended to bring about elimination of the state in the chip memory 6. Simultaneously with this operation a random number generator (mot shown) component of the means 28 can be started, said generator being coded by the credit card company. Then joint operation of the credit card information and the random

15

20

25

30

number code will advise that the card besides being serviceable also is valid, a piece of information which is valuable to the point of sale and also constitutes to the credit card company a confirmation of transaction. As a matter of fact, if necessary the memory contents can be periodically read by the credit card company when the press copying machine is checked, e.g. at service.

Triggering the code for extinguishing the state introduced into the memory 6 of the chip circuit 4 can of course be brought about in another way than by actuating again the change-over switch 30 when the mechanism 21 is returned to its starting position. For example, reading the state per se could form the basis of triggering the extinguishing procedure. The essential point is that the card is unfit for use when removed from the machine 18.

Within the scope of the invention the state(s) imparted to the memory 6 to make the card serviceable can include further information possibly necessary to the points of sale. In such cases the indicating unit is to be adjusted to growing demands for information.

As a matter of course, the activating device 12 shown in Fig. 3 could be designed in many ways within the scope of the invention. Suitably it is made plane to fit a credit card and a place where to keep it, e.g. a wallet. It is conceivable that the introduction of states can be initiated by other means than by push buttons 13-16. Here modern technics offer many solutions. Suitably the chip circuit is designed such that a state transferred thereto and stored therein has a timely limited duration in order to prevent unauthorized use of an activated card during a period of time longer than that requested for concluding a normal registration procedure at a point of sale.

15

20

25

Claims

1. Handling system for information carriers, in particular so called credit cards and the like, including information storing means externally communicable, characterized by a first (Fig. 3) and a second (Fig. 4) transmission device, with which devices said information storing means (4, 5, 6) can be brought to communicate in such a way that said first device (Fig. 3) imparts to the means (4) one or more states which, when the means cooperates with said second device (Fig. 4), can be read (9) and possibly stored by said second device which, under predetermined conditions, can affect the means in order to eliminate the state or states or, alternatively, to introduce a different state.

- 2. Handling system according to claim 1, characterized in that said first transmission device (Fig. 3) is arranged as a signal transmitter for cooperation with the information storing means (4, 6) to activate the same by introducing (13, 14, 15, 16) a code of authority state.
- 3. Handling system according to claim 2, <u>characterized in that</u> the code of authority is arranged to be released by a sequential actuation of operating means (13, 14, 15, 16).
- 4. Handling system according to any of the preceding claims, characterized in that said second transmission device (Fig. 4) includes an information reader as well as a signal transmitter (28), the information reader being programmed such that when detecting correct authority code an indication (34, 35) is re-

leased.

- 5. Handling system according to claim 4, characterized in that the signal transmitter (28) is caused, after the authority code has been detected, to initiate an elimination code to eliminate the state of signal in the memory (6) of the signal storing means (4).
- 6. Handling system according to claim 4, <u>characterized in that</u> the signal transmitter (28) is caused, after the authority code has been detected, to initiate introduction of a differing state.
- 7. Handling system according to any of the preceding claims, characterized in that said first transmission device (12-17) includes operating means (1316) and transmitter circuits (17) for releasing and transmitting a plurality of code signals to the information storing means (4, 6), resulting in one or more states (8).
- 8. Handling system according to any of the preceding claims, characterized in that said second transmission device (28, 29) is capable of locking as well as storing information from the information storing means (6) for further handling or transmitting.
- 9. Handling system according to any of the preceding claims, characterized in that said second transmission device (Fig. 4) is included in a press copying machine (18) for credit cards and the like, the transmission device (28, 29) being functional—

ly initiated (30, 31, 32) by the press copying mechanism (21) moving along its path of operation (19).

- 10. Handling system according to claim 9, <u>characterized in that</u> an indicating device (34) for indicating a state read is connected to the transmission device (28).
- 11. Handling system according to claim 9 or 10, <u>characterized</u> in that the press copying machine is provided with means for reading further information, optically (2) or magnetically (3) stored in the credit card or the like, for possible handling in connection with remaining information obtained.
- 12. Handling system according to any of the preceding claims,

 characterized in that said second transmission device also includes a coded random number generator and that the state(s)

 introduced into the information storing means (4) include record information which, when joint handled with states of random number code obtained, will result in information for control.

Fig. 1




Fig. 2






Fig. 3





INTERNATIONAL SEARCH REPORT

International Application No PCT/SE 90/00032

			Title Hattoner Application No 1 O1	752 307 00052
	_			
			National Classification and IPC	•
11703:	6 00 K	19/067, G 07 F 7/10		
II CIELS	C CCAROU			`
II. FIELD	S SEARCH			
		Minimum Docum		
Classificat	ion System		Classification Symbols	
		·	•	
IPC5	. •	G 07 C; G 07 F; G 06 K		
	•			· · · · · · · · · · · · · · · · · · ·
		to the extent that such Docume	or priority date and not in conflict with the application but cited to understand the principle or theory understand the considered to involve an invention cannot be considered to provide an inventive step when the comments, such combined with one or more other such documents, such combination being obvious to a person skilled in the art.	
ו פב חעו	ET NO -	lancas as about	•	,
3E,UK,I	ri,NU C	lasses as above		
III. DOCU	MENTS CO	ONSIDERED TO BE RELEVANT?		:
Category *	Citati	on of Document 11 with indication, where a	namerica of the relevent necessor 12	Relevant to Claim No 13
	 			
A		, 3632294 (SIEMENS AG) 7	April 1988,	1-3,/
		e figure 1		
	se	e the whole document	•	
			· :	
A	EP, A1	, 0291834 (OKI ELECTRIC :	INDUSTRY COMPANY,	1
	LI	MITED) 23 November 1988,		
	se	e column 1, line 15 - co	olumn 2.	
	1i.	ne 29; abstract; figure	es 1A.1B.2	
			•	
			·	,
,				
		•		
		· ·		·
-				
		•	·	
1			,	
		·	•	
(•		
	•			
			•	
3 Specia	Leatogorio	s of cited documents; 10		
			or priority date and not in conflict	ne international filing date ct with the application but
		ng the general state of the art which is not e of particular relevance	invention	or theory underlying the
"E" earli filin	ier documen g date	t but published on or after the internationa	"X" document of particular relevance	, the claimed invention
"L" docu	- Iment which	may throw doubts on priority claim(s) or	involve an inventive step	innot be considered to
. whic	h is cited to ion or other	may throw doubts on priority claim(s) or establish the publication date of another special reason (as specified)	"Y" document of particular relevance	, the claimed invention
		ing to an oral disclosure, use, exhibition or	accument is combined with one	or more other such docu-
othe	r means		ments, such combination being of in the art.	povious to a person skilled
"P" docu later	ment publis	hed prior to the international filing date bu iority date claimed		atent family
IV. CERTIF		,		
		oletion of the International Search	Date of Mailing of this International Se	arch Report
			1990 -02- 2	;
l6th Au	gust 19	90	1000 -00- 2	
Intomatica	1 Casa-5 '-	· · · · · · · · · · · · · · · · · · ·		
Internationa	i searching	Authority.	Signature of Augustized Officer	_
	SWEDI	SH PATENT OFFICE	BARSUJAKOBSSUNUS 2	~ ·
		· · - -	1 " <i>TI</i> ""	1

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 90/00032

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 90-06-27 The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
DE-A1- 3632294	88-04-07	NONE		
EP-A1- 0291834	88-11-23	JP-A- JP-A-	63282899 1129376	88-11-18 89-05-22